

Lithium-ion battery power system

51.2V100Ah (48100W)

This series is a complete solution for the lithium iron phosphate battery system for the home energy storage field. There are three types of wall-mounted, vertical structures and rack. The system is safe and reliable. It can be used in home storage, industrial and commercial energy storage and other fields.

Characteristic

• Safe, reliable and long life

- Dynamic identification, automatic paralleling, no need for DIP switches
- Support Bluetooth, mobile APP switching PCS protoco
- CAN/RS485/LAN interface
- Visualization, LCD screen display
- Flexible expansion, the number of parallel machines supports up to 15
- Supports mixed parallel of old and new batteries
- Remote intelligent upgrade maintenance





MENU ENTER

O DOWN



Panel silkscreen preview

CAN RS485 IN







OUT

Dry contact



Battery communication interface preview


System Specifications


| Voltage(V) | | 43.2~58.4V |
|------------------------------|----------|----------------|
| Cell | | 3.2V100Ah |
| Module | | 16S1P |
| Number of parallel machines | | 15PCS |
| Nominal voltage(V) | | 51.2 |
| Nominal Capacity(Ah) | | 100 |
| Nominal Energy(kWh) | | 5.12 |
| Maximum power output(kW) | | 5.12 |
| Maximum discharge current(A) | | 100 |
| Maximum charging current(A) | | 100 |
| Cut-off voltage(V) | | 40 |
| Maximum charge voltage(V) | | 58.4 |
| Cycles(25°C) | | ≥6000 |
| Charging temperature(°C) | | 0~55 |
| Discharge temperature(°C) | | -20~55 |
| Operating humidity | | <95%R.H |
| Communication mode | | CAN/RS485 |
| Dry contact | Customiz | zed by demand |
| Optional modules | Blueto | oth, 4G module |
| Product size(W*D*H, | mm) | 580*415*150 |
| Packing size(W*D*H,mm) | | 652*487*265 |
| Protection class | | IP21 |
| System weight(kg) | | Approx 50 |
| Certification IEC62619/U | | /UN38.3/MSDS |
| | | |


Product renderings




Cell characteristic curve









With process improvements and product upgrades, the product parameters are subject to change without prior notice

Version: 202307